MATERIAL SAFETY DATA SHEET

SECTION 01 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION:

Chemical Name:

NUFLEX® 110 BUTYL RUBBER CAULK AND GUTTER

SEAL

Manufacturer:

NUCO INC.

June 26, 2003

150 Regai Road Guelph, Ontario N1K 189

Tel: (519)-823-4994 Fax: (519)-823-1099

infotrac 24 Hour Emergency Tel: (800)-535-5053

Date:

Prepared by:

Technical Services Department

B3. D2B

WHMIS Classification: Product Use:

Caulking compound

SECTION 02 - COMPOSITION / INFORMATION ON INGREDIENTS;

Ingredients CAS No. % LD50(Oral-rat) LC50(Inhalation-rat)

Mineral Spirits 8052-41-3 10.0 - 30.0 Not available Not available

The ingredient listed above are controlled products as defined in CPR, am. SOR/88-555 or 29 CFR 1910.1200

SECTION 03 - HAZARDS INDENTIFICATION:

ROUTES OF ENTRY INTO THE BODY (ACUTE EFFECTS):

Eyes:

Direct contact may cause mild irritation.

Skin:

May cause slight irritation. Symptoms may include localized redness,

swelling and itching.

inhalation:

irritates respiratory passages very slightly. Overexposure may cause upper respiratory tract irritation, headache, dizzlness, drowiness, and

slowed reaction time.

ingestion:

Low ingestion hazard in normal use. Irritation may cause abdominal pain,

nausea, diarrhea and vomiting.

WHMIS HAZARD SYMBOL(S):





SECTION 04 - FIRST AID MEASURES:

Eyes:

Flush with copious quantities of lukewarm water. Do not attempt to physically remove the solids or gums from the eye. Seek medical attention

immediately.

Skin:

Remove contaminated clothing. Wash thoroughly with warm water and

non-abrasive soap. Seek medical attention if you feel ill or a reaction

develops.

Inhalation:

Remove to fresh air and provide water. Seek medical attention if you feel

ill or a reaction develops.

Ingestion:

Get medical attention.

SECTION 05 - FIRE FIGHTING MEASURES:

Flammable Conditions:

Avoid direct sources of heat or ignition in uncured state. Solvent vapors are heavier than air and may travel along the ground and be ignited by

sources distant from handling points.

Extinguishing Media:

Carbon dioxide, dry chemical, water fog or foam. Water can be used to

cool fire exposed containers.

Fire Fighting Measures:

Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate

or isolate the area according to your local emergency plan.

SECTION 12 - ECOLOGICAL INFORMATION:

Air: Water: Complete information is not yet available. Complete information is not yet available. Complete information is not yet available.

Soll:

SECTION 13 - DISPOSAL CONSIDERATIONS:

Waste Disposal:

Dispose in accordance with Federal, State / Provincial and local

regulations.

SECTION 14 - TRANSPORT INFORMATION:

Shipping Information:

DOT PROPER SHIPPING NAME: Adhesives containing Flammable Liquid.

DOT HAZARD CLASS: UN 1133

IDENTIFICATION NO.: NMFC Item No. 149610

TDG CLASSIFICATION: Class 3.3, Packing Group III (General Exemption

1.33 for Domestic Shipments).

SECTION 15 - REGULATORY INFORMATION:

TSCA Inventory Status:

Chemical components listed on TSCA inventory except as exempted.

NFPA Profile:

Health 1, Flammability 2, Reactivity 0

SARA TITLE III Chemical Listings:

Section 302 Extremely Hazardous Substances: None Section 304 CERCLA Hazardous Substances: None

Section 312 Hazard Class: Acute: Yes; Chronic: Yes; Fire: Yes; Pressure:

No; Reactive: No

Section 313 Toxic Chemicals:

None present or none present in

State Substance List:

raportable quantities. This product contains a listed substance(s) that appears on one or more of the Substance Lists for Pennsylvania, Massachusetts and New Jersey:

mineral spirits (CAS# 8052-41-3).

California Proposition 65 List:

Volatile Organic Content:

None known 130 grams per liter (1.08 lb/gallon), 8.67% by weight.

WHMIS Classification:

83, D2B

Chemical components listed on DSL except as exempted. Domestic Substance List:

SECTION 16 - OTHER INFORMATION:

The information herein is given in good faith, but no warranty, express or implied, is made. Product users should make independent judgements of the suitability of this information to ensure proper use and to protect the health and safety of employees.

Form: MSNUFLEX110 Rev.: 2 Date: 06/03